www.airblast.com

Airblast B.V.
P.O. Box 1075
1700 BB Heerhugowaard
The Netherlands
Tel. : +31 72-5718002
Fax : +31-72-5714340
E-mail : info@airblast.com

Commercial Information
The Art of Powerful Cleaning...

Version / Date: 01 / 0903

Title: Airblast Abrasive Valves

The **Airblast ATV, AMV** and **ACV** abrasive valves guarantee unmatched performance, dependability and durability. Developed for the latest abrasives such as Garnet. Using considerable less abrasives, if compared with the older type FSV valves, combined with maximum blasting productivity and reduced downtime. The valves can easily be fitted to most major brands of abrasive blasting equipment. Our valves help you keep your competitive edge!

Airblast ATV

Use this normally closed, self sealing, abrasive metering valve under those circumstances where you require an instant and smooth response to either pneumatic or electric deadman controls. The ATV valve shuts off media flow to the nozzle and seals the blast machine at the same time. Use the available remote abrasive cutoff allowing you the operator to stop the flow of media while continuing a constant flow of air. Ideal for multiple outlet use and can easily be fitted to most blasting systems. Standard urethane sleeve for normal operation, or optional tungsten carbide sleeve for extended life. Rugged, non-corrosive body.

Airblast AMV

Maximum control of the quantity of all abrasive blast media. Constant abrasive media flow with one knob. Easy maintenance, hardened stainless steel plunger and urethane sleeve for fine adjustment and less downtime. Use the AMV to replace Flat Sand Valves (FSV) and all other type of less economic valves. Makes your blast system a more profitable piece of equipment with a considerable reduced consumption of abrasive.

Airblast ACV

The Airblast Combi Valve is an normally closed, self sealing, fail safe valve and known for its instant, and good response to either electric or pneumatic remote controls. The combination of the air inlet valve and blowdown valve functions are controlled simultaneously by this valve, eliminating premature failure of the blowdown system. It eliminates the need for abrasive traps, expensive plungers and diaphragms that can require frequent, unscheduled and costly downtime. Service and repair can be performed without removing the valve, and an inexpensive blowdown hose can be replaced in just a few minutes. The valve operates on 50-150 psi air pressure and will retro fit to most existing blastequipment. In certain applications, its unique design can eliminate potential safety hazards from the operation area by simply extending the blowdown hose out of harm's way. The Airblast Combi Valve has a innovative design and quality construction for rugged durability.