

**Airblast B.V.**  
P.O. Box 1075  
1700 BB Heerhugowaard  
The Netherlands  
Tel. : +31 72-5718002  
Fax : +31-72-5714340  
E-mail : info@airblast.com

**Commercial Information**  
*The Art of Powerful Cleaning...*

**Version / Date:** 01 / 0903

**Title:** Airblast Blast Hose

**Quality Blast Hose** from the world's leading manufacturer at very competitive prices. Airblast hose with its antistatic outer case and lightweight but though internal knitted nylon ply gives the user the best combination of wear, cost and safety benefits.



- BLAST HOSE - HEAVY : Heavy execution, Working Pressure 12 Bar  
Suitable for all abrasives  
WEAR FACTOR 60 mm<sup>3</sup> acc. to DIN 53516
- BLAST HOSE - EXTRA HEAVY : Extra heavy execution, Working Pressure 12 Bar  
For sharp-edged hard abrasives,  
(Aluminium-Oxide, Steel Grit, Glass)  
WEAR FACTOR 36 mm<sup>3</sup> acc. to DIN 53516



- Temperature range : -35° C./ +80° C (ambient temperature)  
Safety factor : 3,5:1
- Tube : NR/SBR/BR, black, smooth, abrasion resistant
- Reinforcement : textile, wrapped
- Cover : SBR, black, smooth, cloth impression

***The Art of Powerful Cleaning...***

