



Tips & Tip Guards

HANDTITE TIP GUARDS

Use with all RAC Tips
(221XXX, 286XXX, LL5XXX and FF5XXX)

243161 For 7/8 in. (22 mm) thread size.
Fits Graco and Titan® guns.

243263 For 11/16 in. (17 mm) thread size.
Fits Graco Pole Guns (older style), ASM® Guns and
Wagner® Guns.

- Accepts RAC 5, RAC IV, Fine Finish RAC or LineLazer RAC Tips in over 100 sizes.
- Aerodynamic design creates a tighter, more consistent pattern while minimizing overspray.
- Virtually eliminates paint build-up, dripping and spitting.
- Seals when hand tightened – no tools required!
- Aluminum nut won't rust.
- Maximum working pressure: 4050 psi (27.9 MPa, 279 bar).



**HandTite Tip Guard
243161**

HEAVY-DUTY RAC TIP GUARDS

Use with Heavy-Duty RAC Tips (GHDXXX).

222674 For 7/8 in. (22 mm) thread size.

- Patented aerodynamic design.
- Extra large tip guard for heavier coatings.
- Tip secured to guard with a screw for safe spraying at higher pressures.
- Maximum working pressure: 5000 psi (34.5 MPa, 345 bar).



**HD RAC Tip Guard
222674**

FLAT TIP GUARDS

Use with Contractor and Silver Flat Tips
(269XXX and 163XXX, Odd #).

220251 For 7/8 in. (22 mm) thread size.
Fits Graco and Titan Guns.

220255 For 11/16 in. (17 mm) thread size.
Fits Graco Pole Guns (older style), ASM Guns and
Wagner Guns.



**Flat Tip Guard
220251**

FINE FINISH FLAT TIP GUARDS

Use with Fine Finish Flat Tips (163XXX, Even #).

220247 For 7/8 in. (22 mm) thread size.
Fits Graco and Titan Guns.

220249 For 11/16 in. (17 mm) thread size.
Use with Pole Guns (older style), ASM Guns,
Wagner Guns, Tip Filter Housings and Swivel
Adapters.



**Fine Finish Flat Tip Guard
220247**

Airless Applicators

Tips & Tip Guards

RAC SwitchTips

Reverse-A-Clean SwitchTips reverse to clear tip plugs for reduced downtime and improved productivity. The SwitchTip design makes tip changes fast and simple.

RAC 5 SWITCHTIP

286XXX Black (Odd#)

- Arrow-shaped handle with contoured grip easily identifies spray versus unplug position.
- General spray tip is ideal for residential, commercial and industrial jobs.
- All RAC 5 SwitchTips feature OneSeal™ design.
- Proprietary spray tip provides consistent pattern and long life.
- Maximum working pressure: 4050 psi (27.9 MPa, 279 bar).



RAC 5 SwitchTip
243XXX

FINE FINISH RAC 5 SWITCHTIP

FF5XXX Green (Even#)

- Dual orifice tip for fine finish with light viscosity coatings.
- Patented, two-stage atomization process creates a soft, feathered spray pattern.
- Produces a smooth, extremely fine finish with consistent material thickness.
- Allows spraying at lower pressures for more control and dramatic overspray reduction.
- Maximum working pressure: 4050 psi (27.9 MPa, 279 bar).



Fine Finish RAC 5 SwitchTip
FF5XXX

LINELAZER RAC 5 SWITCHTIP

LL5XXX Yellow (Odd#)

- Designed specifically for parking lots, roads, warehouse floors, crosswalks and athletic fields.
- Sprays heavy waterbased to thin alkyd traffic paints.
- Ensures consistent paint thickness, less overspray and long-lasting lines.
- Maximum working pressure: 4050 psi (27.9 MPa, 279 bar).



LineLazer RAC 5 SwitchTip
LL5XXX

ONESEAL KITS

243281 5-Pack of OneSeals

- Compatible with all fluids.
- Easy installation without tools.



OneSeal
243281 (5 Pack)



RACPAK
243269

RACPAK™

243269 Includes 517 RAC 5 SwitchTip and HandTite Guard with 7/8 in. (22 mm) thread.

Airless Applicators

Tips & Tip Guards

HEAVY-DUTY RAC SWITCHTIP

GHDXXX Gray (Odd#)

- Recommended for filled materials such as high solids coatings and fibrous mastics.
- Use with virtually all paints and coatings – solvent or waterbased.
- Applications include bridges, tank farms, structural steel and roofing.
- Features a secure, single screw assembly that secures tip to housing (ideal for heavy duty applications).
- Maximum working pressure: 5000 psi (34.5 MPa, 345 bar).



GHDXXX

RAC IV SWITCHTIP

221XXX Black (Odd#)

- General spray tip, ideal for common coatings.
- Choose black rubber gasket (for latex) or yellow gasket (for solvent).
- Maximum working pressure: 4050 psi (27.9 MPa, 279 bar).



221XXX

Flat Tips

CONTRACTOR FLAT TIP

269XXX (Odd#)

- Tungsten carbide orifice for optimum hardness and wear resistance.
- Use filter with smaller sizes to avoid tip plugging.
- Maximum working pressure: 5000 psi (34.5 MPa, 345 bar).



269XXX

SILVER FLAT TIP

163XXX (Odd#)

- For industrial spray applications where tighter tolerances are required.
- Sprays lacquers, varnishes, shellacs and enamels, as well as acrylics, latex, oil bases, blockfillers, epoxies, zinc chromates, roof coatings, mastics and adhesives.
- Maximum working pressure: 5000 psi (34.5 MPa, 345 bar).



163XXX
(odd)

FINE FINISH FLAT TIP

163XXX (Even#)

- Excellent for spraying extremely smooth finishes.
- Sprays varnishes and lacquers as well as modified urethanes and topcoats.
- Pre-orifice provides a fine finish like air spray but with the control of airless.
- Maximum working pressure: 3000 psi (20.7 MPa, 207 bar).



163XXX
(even)