

SUCTION/DISCHARGE HOSE

Heavy duty polyurethane



Airblast range of Suction and Discharge Hoses comprises of the highest quality hoses manufactured and gives you the optimum combination of durability, cost and safety.

Polyurethane hose for air, dust, gasses, smoke, chemical gasses, powders, pulverized products glass- or rockwool. Flexible and kink proof, abbrasion resistant. When bended the hose stays full bore as the PU material is forced to the outside, creating a ful flow without obstruction.

Specifications

Norm : EU 10/2011 Cat. E Temperature range : -25°C / +85°C

Tube : Transparent Polyurethane smooth inside crushproof PVC spiral, corrugated cover

Bending radius $\quad : \quad 1 \times inside diameter$

Airblast offers a full selection of suction and discharge hoses as well as other hoses used in blast cleaning and paint spraying operation – contact Airblast to discuss which hose is most suitable for your specific application.

Poly	vurethane	Suction.	/Discharge Hoses	
	, ai cailaile	Saction	Discharge Hoses	

,,									
Part no.	Description	ID in mm	OD in mm	Vacuum bar	PU-wall in mm	Available lenghts in mtr.			
2518300	Suction/Discharge Hose 51 x 59	51	59	0,3	0,7	20			
2518400	Suction/Discharge Hose 63 x 71	63	71	0,3	0,7	20			
2518500	Suction/Discharge Hose 76 x 85	76	85	0,3	0,7	20			
2518600	Suction/Discharge Hose 102 x 112	102	112	0,3	0,8	20			
2518700	Suction/Discharge Hose 127 x 139	127	139	0,3	0,8	20			
2518800	Suction/Discharge Hose 152 x 165	152	165	0,2	0,8	20			

Email: info@airblast.com • Web: www.airblast.com

© 2014 Airblast B.V. - Doc. nr. LT2043E Rev. A May 2014